



ref. GBPT420

Monitoring gates / security for libraries with buzzer (alarm) and intermittent light.

Optional Features



Gates RFID and Alarm BC

ref. GBPT420

Combined gates via RFID antennas, reader, sound and alarm system activated by light. The BC-GBPT420 portals do all the screening of goods (books, DVD's, CD's, magazines, etc..) attached with an RFID tag. If the application notices that an unauthorized item was included, the local alarm is fired.

Specifications

Frequency range	902-928MHZ (or customized)	GP I/O interface	12 pin + 4 pin
FM mode	FHSS or fixed frequency, set by the software	Dimension	180*35*20cm
RF output	20-30dBm adjustable	Power supply	220V AC input
Antenna connection	4 SMA antenna ports, 7dbi	Weight	20KG
Communication inter.	LAN,RS232, RS485, Wiegand26/34	Humidity	5% to 95%
Communication rate	Serial port 9600~115200bps, RJ45 10Mbps	Certification	CE, FCC
Power dissipation	average<20W	Protection grade	IEC IP51
EAS alarm	3s sound and light prompt	Operation temperature	-20 °C to +60 °C
Reading distance	1.5-3m equipped with 7dbi antenna	Color	White; Custom (opt.)
Reliable firmware upg.	Extensible upgrade mechanism	Storage temperature	-40°C to 80°C

Optional Custom color

